

Technical Data

No.	Model	Voltage	Speed	Max. Flow	Max. Head	Motor Power		Diameter	Max. Solid Dia	N.W	G.W	Packing Dimension
		V	r.p.m	m ³ /h	m	kW	HP	in	mm	kg	kg	mm
1	50WQ4-6-0.18M	380	2900	12	7	0.18	0.25	2"	5	11.1	13.3	414×264×195
2	50WQD4-6-0.18M(A)	220	2900	12	7	0.18	0.25	2"	5	11.3	13.5	414×264×195
3	50WQ5-7-0.25(M)	380	2900	14	8	0.25	0.33	2"	5	15.2	18.6	514×284×228
4	50WQD5-7-0.25(M)(A)	220	2900	14	8	0.25	0.33	2"	5	16	19.2	514×284×228
5	50WQ7-7-0.37(M)	380	2900	15	10	0.37	0.55	2"	15	15.7	18.7	514×284×228
6	50WQD7-7-0.37(M)(A)	220	2900	15	10	0.37	0.55	2"	15	16.2	19.2	514×284×228
7	50WQ6-12-0.55(M)	380	2900	19	15	0.55	0.75	2"	15	16.5	22.3	610×281×231
8	50WQD6-12-0.55(M)(A)	220	2900	19	15	0.55	0.75	2"	15	16.9	22.4	610×281×231
9	50WQ20-6.5-0.75	380	2900	26	13	0.75	1	2"	20	17	19	610×281×229
10	50WQD20-6.5-0.75	220	2900	26	13	0.75	1	2"	20	18	20	610×281×229
11	50WQ6-16-0.75(M)	380	2900	22	19	0.75	1	2"	15	17.4	22.9	610×281×231
12	50WQD6-16-0.75(M)(A)	220	2900	22	19	0.75	1	2"	15	17.9	23.4	610×281×231
13	50WQ10-10-0.75(M)	380	2900	19	15	0.75	1	2"	20	17.2	22.7	610×281×231
14	50WQD10-10-0.75(M)(A)	220	2900	19	15	0.75	1	2"	20	17.8	23.3	610×281×231
15	50WQ10-16-1.1	380	2900	30	19	1.1	1.5	2"	25	24.5	30.3	651×311×246
16	50WQD10-16-1.1(A)	220	2900	30	19	1.1	1.5	2"	25	25.4	31.3	651×311×246
17	50WQ15-10-1.1	380	2900	27	12.5	1.1	1.5	2"	25	23.9	29.7	651×311×246
18	50WQD15-10-1.1(A)	220	2900	27	12.5	1.1	1.5	2"	25	24.9	30.7	651×311×246
19	50WQ20-10.5-1.1	380	2900	26	16.5	1.1	1.5	2"	20	24	26	610×281×229
20	50WQD20-10.5-1.1	220	2900	26	16.5	1.1	1.5	2"	20	25.6	27.6	651×311×244
21	65WQ15-10-1.1	380	2900	31.5	13	1.1	1.5	2½"	25	24.5	31.2	651×311×246
22	65WQD15-10-1.1(A)	220	2900	31.5	13	1.1	1.5	2½"	25	25.5	32.2	651×311×246
23	50WQ10-20-1.5	380	2900	33	21.5	1.5	2	2"	25	27	32.8	544×269×244
24	50WQD10-20-1.5(A)	220	2900	33	21.6	1.5	2	2"	25	29.8	35.8	604×269×244
25	50WQ15-15-1.5	380	2900	32	18.5	1.5	2	2"	25	26.3	32.1	544×269×244
26	50WQD15-15-1.5(A)	220	2900	32	18.5	1.5	2	2"	25	29.2	35.2	604×269×244
27	50WQ20-14-1.5	380	2900	26	20.5	1.5	2	2"	20	27	34	544×269×244
28	50WQD20-14-1.5	220	2900	26	20.5	1.5	2	2"	20	25	32	604×269×244
29	50WQ30-10-1.5	380	2900	39	16	1.5	2	2"	25	24	30	544×269×244
30	50WQD30-10-1.5	220	2900	39	16	1.5	2	2"	25	25	31	604×269×244
31	65WQ15-15-1.5	380	2900	39.7	20	1.5	2	2½"	25	27	31.7	544×269×244
32	65WQD15-15-1.5(A)	220	2900	39.7	20	1.5	2	2½"	25	29.8	36.7	604×269×244

Technical Data

No.	Model	Voltage	Speed	Max. Flow	Max. Head	Motor Power		Diameter	Max. Solid Dia	N.W	G.W	Packing Dimension
		V	r.p.m	m³/h	m	kW	HP	in	mm	kg	kg	mm
33	50WQ10-25-2.2	380	2900	13	28.5	2.2	3	2"	20	28	34	604×269×244
34	50WQ15-20-2.2	380	2900	36	24	2.2	3	2"	20	31.5	38.4	604x269x244
35	65WQ15-20-2.2	380	2900	41.6	24.6	2.2	3	2½"	25	30.9	36.9	604x269x244
36	80WQ40-9-2.2	380	2900	63	17	2.2	3	3"	30	32.3	39.9	604x269x244
37	50WQ18-25-3	380	2900	42	29	3	4	2"	20	43	51.3	744x324x289
38	65WQ25-22-3	380	2900	50	29	3	4	2½"	25	43.7	52.9	744x324x289
39	80WQ40-13-3	380	2900	70	20	3	4	3"	30	45	54.9	744x324x289
40	100WQ60-9-3	380	2900	75	16	3	4	4"	30	46.8	60.2	744x324x289
41	50WQ18-32-4	380	2900	45	36	4	5.5	2"	20	48	56.3	744x324x289
42	65WQ25-28-4	380	2900	51	31.5	4	5.5	2½"	25	48.6	57.8	744x324x289
43	80WQ40-18-4	380	2900	79	21	4	5.5	3"	30	50	59.9	744x324x289
44	100WQ60-13-4	380	2900	85	20	4	5.5	4"	30	52.1	65.3	744x324x289
45	50WQ15-40-5.5	380	2900	30	44	5.5	7.5	2"	20	95	114	904x399x439
46	80WQ30-30-5.5	380	2900	70	35	5.5	7.5	3"	30	93	113	904x399x439
47	80WQ50-15-5.5/4	380	1450	70	25	5.5	7.5	3"	30	142	169	1240x460x500
48	100WQ45-22-5.5	380	2900	100	28	5.5	7.5	4"	30	93	117	904x399x439
49	100WQ65-15-5.5/4	380	1450	120	18	5.5	7.5	4"	55	145	180	1064x549x520
50	100WQ130-10-5.5/4	380	1450	169	16	5.5	7.5	4"	45	133	161	1064×549×520
51	150WQ110-10-5.5/4	380	1450	260	12	5.5	7.5	6"	75	155	193.5	1064x549x520
52	50WQ20-45-7.5	380	2900	45	50	7.5	10	2"	20	120	139	904x399x439
53	80WQ30-36-7.5	380	2900	75	41	7.5	10	3"	30	118	140	1054x399x439
54	100WQ65-22-7.5	380	2900	108	31	7.5	10	4"	35	120	145	1054x399x439
55	150WQ100-10-7.5	380	2900	150	20	7.5	10	6"	35	125	157	1054x399x439
56	80WQ45-22-7.5/4	380	1450	80	26	7.5	10	3"	30	150	177	1064x549x520
57	100WQ100-15-7.5/4	380	1450	140	21	7.5	10	4"	55	150	180	1064x549x520
58	100WQ150-11-7.5/4	380	1450	195	18	7.5	10	4"	45	142	170	1064×549×520
59	150WQ150-10-7.5/4	380	1450	300	16	7.5	10	6"	75	160	197	1064x549x520
60	200WQ250-6-7.5/4	380	1450	325	12.5	7.5	10	8"	50	176	205	1164×579×589
61	50WQ20-55-11	380	2900	45	60.5	11	15	2"	25	136	158.5	1040x420x477
62	50WQ30-50-11	380	2900	45	60.5	11	15	2"	25	136	158.5	1040x420x477

Technical Data

No.	Model	Voltage	Speed	Max. Flow	Max. Head	Motor Power		Diameter	Max. Solid Dia	N.W	G.W	Packing Dimension
		V	r.p.m	m³/h	m	kW	HP	in	mm	kg	kg	mm
63	65WQ50-40-11	380	2900	65	47.5	11	15	2½"	30	138	158	1040×420×477
64	80WQ45-40-11	380	2900	60	50.5	11	15	3"	30	131	155	1040x420x477
65	80WQ70-30-11	380	2900	100	40.5	11	15	3"	30	137	161	1040x420x477
66	100WQ80-26-11	380	2900	120	42	11	15	4"	35	132	159	1040x420x477
67	100WQ100-25-11/4	380	1450	220	31	11	15	4"	50	252.5	281.5	616x520x1388
68	150WQ120-18-11	380	2900	160	30	11	15	6"	55	137	171	1040x420x477
69	150WQ130-20-11/4	380	1450	169	29.5	11	15	6"	45	348	370	616×516×1388
70	150WQ180-11-11/4	380	1450	260	24	11	15	6"	60	264	300	616x520x1388
71	150WQ180-15-11/4	380	1450	234	29.5	11	15	6"	50	300	322	616×516×1388
72	200WQ300-7-11/4	380	1450	450	17	11	15	8"	70	285	314	716x620x1488
73	200WQ400-5-11/4	380	1450	470	18	11	15	8"	55	285	314	716x620x1488
74	250WQ370-8-11/4	380	1450	481	16.5	11	15	10"	50	348	377	716×616×1488
75	50WQ20-70-15	380	2900	45	75.5	15	20	2"	25	150	172.5	1040x420x477
76	50WQ30-65-15	380	2900	45	75.5	15	20	2"	25	150	172.5	1040x420x477
77	65WQ50-46-15	380	2900	65	56	15	20	2½"	30	144	164	1040×420×477
78	80WQ50-48-15	380	2900	65	56.5	15	20	3"	30	137	157	1040×420×477
79	80WQ50-55-15	380	2900	65	62.5	15	20	3"	30	145	165	1040×420×477
80	80WQ70-40-15	380	2900	100	49.5	15	20	3"	30	149	173	1040x420x477
81	100WQ100-30-15/4	380	1450	220	36	15	20	4"	50	273	302	616x520x1388
82	150WQ100-30-15	380	2900	130	50	15	20	6"	35	152	177	1240×460×497
83	150WQ150-23-15/4	380	1450	195	34	15	20	6"	45	307	329	616×516×1388
84	150WQ200-15-15/4	380	1450	290	29	15	20	6"	60	285	321	616x520x1388
85	200WQ250-11-15/4	380	1450	490	21	15	20	8"	70	305.5	334.5	716x620x1488
86	200WQ400-8-15/4	380	1450	525	19	15	20	8"	55	305.5	334.5	716x620x1488
87	250WQ400-10-15/4	380	1450	520	19	15	20	10"	50	355	383	716×616×1488
88	50WQ20-80-18.5	380	2900	45	85.5	18.5	22	2"	25	217.5	245	1240x460x500
89	50WQ30-75-18.5	380	2900	45	85.5	18.5	22	2"	25	217.5	245	1240x460x500
90	80WQ55-58-18.5	380	2900	71.5	67.5	18.5	22	3"	30	212	237	1240×460×497
91	80WQ70-50-18.5	380	2900	100	58.5	18.5	22	3"	30	212.5	241.5	1240x460x500
92	100WQ90-43-18.5	380	2900	117	57.5	18.5	22	4"	35	213	238	1240×460×497

Technical Data

No.	Model	Voltage	Speed	Max. Flow	Max. Head	Motor Power		Diameter	Max. Solid Dia	N.W	G.W	Packing Dimension
		V	r.p.m	m ³ /h	m	kW	HP	in	mm	kg	kg	mm
93	100WQ100-33-18.5/4	380	1450	220	39	18.5	25	4"	50	293	322	616x520x1388
94	150WQ150-25-18.5/4	380	1450	300	32	18.5	25	6"	60	305.5	341.5	616x520x1388
95	200WQ300-13-18.5/4	380	1450	530	25	18.5	25	8"	70	325.5	354.5	716x620x1488
96	200WQ400-10-18.5/4	380	1450	525	22	18.5	22	8"	55	325.5	354.5	716x620x1488
97	250WQ600-6-18.5/4	380	1450	750	18	18.5	22	10"	75	354	383	716x620x1488
98	50WQ20-90-22	380	2900	45	94	22	30	2"	25	225	252.5	1240x460x500
99	50WQ30-85-22	380	2900	45	94	22	30	2"	25	225	252.5	1240x460x500
100	80WQ60-62-22	380	2900	78	67.5	22	30	3"	30	254	279	1240x460x497
101	80WQ70-55-22	380	2900	100	63	22	30	3"	30	219	248	1240x460x500
102	100WQ100-36-22/4	380	1450	220	42	22	30	4"	50	298.5	327.5	616x520x1388
103	100WQ100-50-22	380	2900	130	65	22	30	4"	35	256	281	1240x460x497
104	100WQ130-35-22	380	2900	169	62.5	22	30	4"	35	255	280	1240x460x497
105	150WQ100-40-22	380	2900	130	60.5	22	30	6"	35	262	287	1240x460x497
106	150WQ150-30-22/4	380	1450	330	39	22	30	6"	60	312	348	616x520x1388
107	200WQ300-17-22/4	380	1450	550	27	22	30	8"	70	331.5	360.5	716x620x1488
108	200WQ400-13-22/4	380	1450	525	24.5	22	30	8"	55	331.5	360.5	716x620x1488
109	250WQ600-7-22/4	380	1450	800	22	22	30	10"	85	360	389	716x620x1488
110	150WQ150-34-30/4	380	1450	310	45	30	40	6"	55	497	519	780x600x1430
111	200WQ300-21-30/4	380	1450	570	33	30	40	8"	80	519	541	820x620x1470
112	250WQ500-14-30/4	380	1450	860	27	30	40	10"	85	512	535	780x650x1490
113	300WQ800-8-30/4	380	1450	1040	22	30	40	12"	90	557	581	860x720x1540
114	150WQ150-40-37/4	380	1450	330	50	37	50	6"	55	557	579	780x600x1480
115	200WQ300-25-37/4	380	1450	620	39	37	50	8"	80	576	598	820x620x1520
116	250WQ500-18-37/4	380	1450	930	30	37	50	10"	85	570	593	780x650x1540
117	300WQ800-11-37/4	380	1450	1060	25	37	50	12"	90	614	638	860x720x1590
118	200WQ300-30-45/4	380	1450	660	43	45	60	8"	80	612	634	820x620x1520
119	250WQ500-21-45/4	380	1450	950	34	45	60	10"	85	606	629	780x650x1540
120	300WQ800-14-45/4	380	1450	1080	28	45	60	12"	90	650	674	860x720x1590